

1. ELECTRICAL SPECIFICATIONS

Accuracy in indicated as \pm (% of reading + number of digits) at $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$; $<60\%$ HR

Earth Resistance 3-wire and 2-wire systems

Range (Ω)	Resolution (Ω)	Accuracy	
		Disturbance $\leq 3\text{Vrms}$	$3\text{Vrms} < \text{Disturbances} < 6\text{Vrms}$
0.01 \div 19.99	0.01	$\pm(2.0\% \text{rdg} + \text{dgt})$	$\pm(4.0\% \text{rdg} + 10\text{dgt})$
20.0 \div 199.9	0.1		
200 \div 1999	1		
2.00k \div 19.99k	0.01k	$\pm(3.0\% \text{rdg} + 3\text{dgt})$	$\pm(6.0\% \text{rdg} + 10\text{dgt})$
20.0k \div 49.9k	0.1k		

Test current: $\leq 12\text{mAAC}$
 Open circuit voltage: $\leq 25\text{V ACTRMS}$
 Test frequency: $110\text{Hz} \pm 1\text{Hz}$

Noise Voltages

Range (V)	Resolution (V)	Accuracy
0.0 \div 99.9	0.1	$\pm(2.0\% \text{rdg} + 2\text{dgt})$
100 \div 299	1	

2. GENERAL SPECIFICATIONS

DISPLAY:

Features: Custom LCD
 Visible area: 53x53 mm

POWER SUPPLY:

Batteries: 4x1.5V battery type LR6-AA-AM3-MN 1500
 Low batteries indications: "🔋" symbol at display
 Batteries life: about 500 test
 AutoPowerOFF: after 5 min from last action

MECHANICAL FEATURES:

Dimensions: 240(L) x 100(W) x 45(H) mm
 Weight (included batteries): about 0.6kg

WORKING ENVIRONMENTAL CONDITIONS:

Reference temperature: $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$
 Working temperature: $0^{\circ} \div 40^{\circ}\text{C}$
 Allowed relative humidity: $<80\%$ HR
 Storage temperature: $-10 \div 60^{\circ}\text{C}$
 Storage humidity: $<80\%$ HR

GENERAL REFERENCE STANDARDS:

Safety of measuring instruments: IEC / EN61010-1, IEC / EN61557-1, IEC / EN61557-5
 Technical documentation: IEC / EN61187
 Safety standard accessories: IEC / EN61010-031, IEC / EN61010-2-032
 Insulation: double insulation
 Pollution degree: 2
 Overvoltage category: CAT III 265V to ground, max 415V between inputs
 Max altitude: 2000m
 EMC: EN61326-1

This instrument complies with the requirements of the European Low Voltage Directives 72/23/CEE (LVD) and EMC 89/336/CEE, amended with 93/68/CEE