



Sample photo

Dimensions:	Length	Width	Height
mm:	130	80	60
inch:	5.1	3.1	2.4

Materials:	
Material:	ABS
Base colour:	RAL 7035
Cover colour:	Smoked grey
Cover screws material:	Polyamide
Cover screws colour:	Black
Gasket material:	TPE

Temperatures:	
Short term:	-40 ... 80 °C
Continuous:	-40 ... 60 °C
Short term:	-40 ... 175 °F
Continuous:	-40 ... 140 °F

Accessories:	
MIV 100	Mounting plate (Galvanized steel)
MIN 5	DIN-15 Mounting rail
MIN 10	DIN-15 Mounting rail
MIV 5	DIN-35 Mounting rail
MIV 10	DIN-35 Mounting rail
FP A 100/130	Front plate (Aluminium)
HFP 130	Front plate hinge series (2 pcs)
FP 22046	Wall fastening lug (4 pcs)

Rating:

Ingress Protection (EN 60529): IP 66/67
 Impact Resistance (EN 62262): IK 07
 Electrical insulation: Totally insulated
 Halogen free (DIN/VDE 0472, Part 815): Yes
 Flammability Rating (UL 746 C 5): UL 94 HB
 Glow Wire Test (IEC 695-2-1) °C: 650
 NEMA Class: NEMA 1, 4, 4X, 6

Certificates:

Fimko
 Europe EN 50298: 1998
 Gost R

