

IoT Wireless Temperature and Relative Humidity Datalogger with connector for other temperature probe, with built-in GSM modem and Flat Rate SIM Card

code: U3631Msim



IoT Wireless Datalogger kit with built-in GSM modem and Flat Rate SIM Card allows the instant connection to the COMET Cloud.

Measured values can be sent to the internet storage [COMET Cloud](#), which is a complete monitoring, alarm and analysis system. IoT Datalogger is designed to record temperature and humidity from built-in sensors and temperature from external probe. In case of exceeded set limits, SMS and JSON messages can be sent via GPRS data connection.

It is also possible to set the regular sending of JSON messages to COMET Database, the sending interval is adjustable. Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper.

The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

GSM recorder **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard**.

Technical data

TEMPERATURE SENSOR	
Measuring range	-20 to +60 °C
Accuracy	±0.4 °C
Resolution	0.1 °C
TEMPERATURE SENSOR - external probe Pt1000	
Measuring range	-90 to +260 °C
Accuracy	±0.2 °C (-50 to +100 °C); ±0.2 % from reading from +100 to +260 °C; ±0.4 % from reading from -90 to -50 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	± 1.8 % RH
Resolution	0.1% RH
DEW POINT	
Measuring range	-90 to +60 °C
Accuracy	±1.5 °C at ambient temperature T <25 °C and RH >30 %
Resolution	0.1 °C
GENERAL TECHNICAL DATA	
Operating temperature	-20 to +60 °C
Channels	internal temperature and humidity sensor, 1x external temperature probe
Memory	500,000 values in noncyclic logging mode; 350,000 values in cyclic record mode
Recording interval	adjustable from 1 s to 24 h
Display and alarm refresh	adjustable 1 s, 10 s, 1 min

Recording mode	noncyclic - data logging stops after filling the memory cyclic - after filling memory oldest data is overwritten by new
Real time clock	year, leap year, month, day, hour, minute, second
Power	battery SONY Lilon 5200mAh
Protection class	IP67 electronics; IP30 sensors
Dimensions	61 x 93 x 53 mm, with antenna 120 x 93 x 53 mm
Weight (including batteries)	approx. 260 g
Warranty	3 years



Zone Acticentre - CRT2 - CS 10210
 156/220 Rue des Famards - 59273 FRETIN
 Téléphone : 03.20.62.06.80
 Télécopie : 03.20.96.95.62
<http://www.dimelco.com>