

Part No.

# NPAK-TRSO

*Liquid trap with male Quick-test top port, female Quick-test bottom port*

Eliminates unwanted fluid or moisture that can contaminate any gas system.



NPAK-TRSO

## Included Items

- Fluid Trap - Fluid and Moisture Trap (TRAP)
- Top Connection - Male Quick-test outlet port, S.S. (QTHA-3SS0)
- Bottom Connection - Female Quick-test outlet port with drain tube (for NPAK-TRSO), S.S. (QTHA-3SSA-LD)

## Specs/Attributes

Country of origin	USA
Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Vacuum	23 InHg / 77.9 kPa
Materials	Anodized Aluminum, Stainless Steel
Seal Materials	Buna-N, Teflon
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Weight	1.14 lbs / 515 grams
Dimensions	H: 5.5 in (13.97 cm) x W: 2 in (5.08 cm) x D: 2 in (5.08 cm)

## Fluid Trap TRAP

Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Vacuum	23 InHg / 77.9 kPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C

**Fluid Trap** TRAP

Country of origin	USA
Dimensions	H: 2.2 in (5.59 cm) x W: 2.2 in (5.59 cm) x D: 5.5 in (13.97 cm)

**Top Connection** QTHA-3SS0

Country of origin	USA
Materials	Stainless Steel
Max Pressure	5000 PSI / 350 bar / 35 MPa
Seal Materials	Buna-N
Wrench Size	9/16 In

**Bottom Connection** QTHA-3SSA-LD

Materials	Stainless Steel
Seal Materials	Buna-N
Country of origin	USA