

TECHNICAL DATA SHEET



Rel. EN 2-00 - 09/06/22

THT400

PROFESSIONAL IR
CAMERA 640x480pxl
WITH TOUCH-SCREEN

640x480
PIXEL



**TEMPERATURE
RANGE**
-20°\550°



**FUSION
PiP**



THT400 is the new professional thermal imaging camera equipped with a high resolution 640 x 480pxl IR sensor which makes it suitable for use in electrical, mechanical, plumbing, ventilation and refrigeration systems.



THT400

Rel. EN 2-00 - 09/06/22

PROFESSIONAL IR CAMERA
640x480pxl WITH TOUCH-SCREEN



Page 2 of 3

TECHNICAL DATA SHEET

1. IMAGING PERFORMANCE

THERMAL

Detector type	UFPA
Spectral range	8 $\pm$ 14 μ m
Resolution / Pxl size	640 x 480pxl / 17 μ m
Thermal sensitivity/NETD	<0.05°C @ 30°C / 50mK
Field of View (FOV)	31.9° x 25.7°
Focal lens / F-number	13.5mm / 1.0
Minimum focal distance	0.5m
IFOV	1.26mrad
Focusing	Automatic
Image frequency	25Hz
Color palettes	8 Standard + 4 Isotherms

VISIBLE

Integrated camera	2Mpxl, FOV 65°
-------------------	----------------

2. IMAGING/IR VIDEO DISPLAY

Display type	3.5" TFT color, capacitive touch-screen, high brightness
Image mode	IR, Visible, Fusion PiP, Auto Fusion
IR Video	Recording and saving MP4 format
Electronic zoom	x1 $\div$ x32 in continuous way

3. TEMPERATURE MEASUREMENT

RANGE	RESOLUTION	ACCURACY (*)
-20°C $\div$ 550.0°C	0.1°C	$\pm$ 2%rdg or $\pm$ 2°C (higher value)
-4.0°F $\div$ 1022.0°F	0.1°F	$\pm$ 2%rdg or $\pm$ 3.6°F (higher value)

(*) Ambient temperature: 10°C $\div$ 35°C, Object temperature: >0°C

4. TEMPERATURE MEASUREMENT SCREENING MODE

RANGE	RESOLUTION	ACCURACY
32.0°C $\div$ 42.0°C	0.1°C	$\pm$ 0.5°C
89.6°F $\div$ 107.6°F	0.1°F	$\pm$ 0.9°F



THT400

Rel. EN 2-00 - 09/06/22

PROFESSIONAL IR CAMERA
640x480pxl WITH TOUCH-SCREEN



Page 3 of 3

TECHNICAL DATA SHEET

5. GENERAL SPECIFICATIONS

Measurement cursors	4 (1 fixed central + 3 freely positionable on image)
Measurement modes	Automatic / Manual / Histogram
Emissivity correction	0.01 ÷ 1.00 + internal table with common materials
Measurement functions	Automatic correction based on distance, relative humidity, ambient temperature, reflexed temperature, offset
Advanced analysis	Spots (max3), Lines (max 2), Areas (max 3), "Hot/Cold" points, Face mode temperature detection (max 10 persons)
Alarm on temperature	Associated to measurements spots
Temp. Compensation	only Screening mode
Operating temperature	-15°C ÷ 50°C
Operating humidity	10%RH ÷ 90%RH
Storage temperature	-40°C ÷ 70°C
Storage humidity	10%RH ÷ 90%RH
Encapsulation	IP54 according with IEC529
Shock	25G, according with IEC60068-2-29
Vibrations	2G, according with IEC60068-2-6
Drop test	2m
Dimensions (L x W x H)	240 x 100 x 110mm
Weight(battery included)	480g

6. IMAGE STORAGE AND EXTERNAL INTERFACE

Memory	Internal memory (3.4GB) + Micro SD card 16GB (max 32GB)
File format	JPEG standard (snapshots), HIR (radiometric)
Memory size	1000 pics/45min video (internal memory), >6000 pics (micro SD)
Textual annotation	With internal virtual keyboard
PC interface	USB-C (download IR images/videos to PC)
WiFi connection	For connection to mobile devices through HTProCamera APP

7. POWER SUPPLY

Battery type	Rechargeable Li-ION, 3,7V 2600mAh
Charging system	In camera
Battery life	Approx. 4 hours (stand-by and WiFi off)
External power	External adapter 100/240VAC (50/60Hz)/5VDC, 2400mA

This instrument complies with European Directive EMC 2014/35/EU and at requirements of European Directives 2011/65/EU (RoHS) and 2012/19/EU (WEEE)



Zone Acticentre – CRT2 – CS 10210
156/220 Rue des Famards - 59273 FRETIN
Tél : 03 20 62 06 80 Fax : 03 20 96 95 62
Mail : contact@dimelco.com

