

1. TECHNICAL SPECIFICATIONS – INSULATION / CONTINUITY

Accuracy is indicated as \pm (% readings + no. of digits) at 23°C \pm 5°C, relative humidity HR <70%

Continuity test on protective and equalizing conductors

Range (Ω)	Resolution (Ω)	Accuracy	Overload protection
0.01 \div 19.99	0.01	$\pm(5.0\% \text{ rdg} + 3\text{dgt})$	605Vrms max
20.0 \div 99.9	0.1		

Test current: > 200mA DC for $R \leq 4\Omega$ (included calibration)
Resolution on current measurement: 1mA

Open-circuit voltage: $4V \leq V_0 \leq 24V$

Insulation Resistance

Range (M Ω)	Resolution (M Ω)	Accuracy	Overload protection
0.00 \div 19.99	0.01	$\pm(5.0\% \text{ rdg} + 2\text{dgt})$	605Vrms max
20.0 \div 199.9	0.1		
200 \div 999(*)	1	$\pm(10.0\% \text{ rdg} + 2\text{dgt})$	

(*) For 500VDC test voltage. For 250VDC test voltage the range is: 200 \div 499M Ω

Test Voltage: 250, 500VDC

Test voltage accuracy: -0% \div +10% rdg

Short circuit current: <3.0mA

Nominal test current: 1mA @ 1k Ω x Vnom ; 1mA @ 500 k Ω

2. TECHNICAL SPECIFICATIONS – MULTIMETER FUNCTIONS

Accuracy is indicated as \pm (% readings + no. of digits) at 23°C \pm 5°C, relative humidity HR <70%

DC VOLTAGE (Autorange)

Range	Resolution	Accuracy	Input impedance	Overload protection
1.0mV \div 999.9mV	0.1mV	$\pm(0.5\% \text{ rdg} + 2 \text{ dgt})$	1M Ω	605Vrms max
1.000V \div 9.999V	1mV			
10.00V \div 99.99V	10mV			
100.0V \div 605.0V	100mV			

AC VOLTAGE TRMS (Autorange)

Range	Resolution	Accuracy (30 \div 70Hz)	Accuracy (70 \div 400Hz)	Input Impedance	Crest factor
1.0mV \div 999.9mV	0.1mV	$\pm(1.0\% \text{ rdg} + 2\text{dgt})$	$\pm(2.0\% \text{ rdg} + 2 \text{ dgt})$	1M Ω	3
1.000V \div 9.999V	1mV				1.5
10.00V \div 99.99V	10mV				
100.0V \div 605.0V	100mV				

AC/DC VOLTAGE: MAX / MIN / AVG / PEAK

Function	Range	Resolution	Accuracy	Response time	
MAX, MIN, AVG	1.0mV \div 999.9mV	0.1mV	$\pm(5.0\% \text{ rdg} + 10\text{dgt})$	500ms	
	1.000V \div 9.999V	1mV			
	10.00V \div 99.99V	10mV			
	100.0V \div 605.0V	100mV			
PEAK	10.0mV \div 999.9mV	0.1mV			1ms
	1.000V \div 9.999V	1mV			
	10.00V \div 99.99V	10mV			
	100.0V \div 605.0V	100mV			

DC/AC CURRENT TRMS (with external clamp)

Range	Resolution	DC Accuracy	Accuracy (30 ÷ 70Hz)	Accuracy (70 ÷ 400Hz)	Crest factor	Overload protection
1.0mV ÷ 999.9mV	0.1mV	±(0.5%rdg+2 dgt)	±(1.0%rdg+2 dgt)	±(2.0%rdg+2 dgt)	3	605Vrms max
1.000V ÷ 1.200V	1mV				1.5	

Note: accuracy indicated don't consider clamp accuracy. Please refer also to transducers clamp user's manual.

AC/DC CURRENT: MAX / MIN / AVG / PEAK (with external clamp)

Function	Range	Resolution	Accuracy	Response time	Overload protection
MAX, MIN, AVG	1.0mV ÷ 999.9mV	0.1mV	±(5.0%rdg+10 dgt)	500 ms	605Vrms max
	1.000V ÷ 1.200V	1mV			
PEAK	10.0mV ÷ 999.9mV	0.1mV		1ms	
	1.000V ÷ 3.000V	1mV			

RESISTANCE AND CONTINUITY TEST

Range	Resolution	Accuracy	Continuity test	Overload protection
0.00Ω ÷ 39.99Ω	0.01Ω	±(1.0%rdg+5 dgt)	R ≤40Ω	605Vrms max for 1 minute
40.0Ω ÷ 399.9Ω	0.1Ω			
400Ω ÷ 3999Ω	1Ω			
4.00kΩ ÷ 39.99kΩ	10Ω			

FREQUENCY (with test leads)

Range	Resolution	Accuracy	Input voltage	Overload protection
30.0 ÷ 199.9Hz	0.1Hz	±(0.5%rdg+2 dgt)	1.0mV ÷ 605V	605Vrms max
200 ÷ 400Hz	1Hz			

FREQUENCY (with external clamp)

Range	Resolution	Accuracy	Input voltage	Overload protection
30.0 ÷ 199.9Hz	0.1Hz	±(0.5%rdg+2dgt)	1.0mV ÷ 1.000V	605Vrms max
200 ÷ 400Hz	1Hz			

PHASE SEQUENCE / CONFORMITY (1 wre measurement)

Type of measure	Voltage range (V)	Frequency range (Hz)	System type
SEQUENCE	90 ÷ 315 (Phase – Earth)	45 ÷ 65	up to 315 (Phase – Earth) up to 550V (Phase – Phase)
CONFORMITY			

PHASE SEQUENCE / CONFORMITY (2 wre measurement)

Type of measure	Voltage range (V)	Frequency range (Hz)	System type
SEQUENCE	110 ÷ 315 (Phase – Neutral)	45 ÷ 65	up to 315 (Phase – Earth) up to 550V (Phase – Phase)
CONFORMITY			

Max crest factor :1.5

NOTE: the two-wire measurement can be performed also phase to phase in plants without neutral, even with one phase to earth, but always with phase to phase voltage up to 550V



3. GENERAL SPECIFICATIONS

DISPLAY:

Features:	Dual numeric, 9999 points
Display update:	2 times/sec
Visible area:	73x73 mm

POWER SUPPLY:

Batteries:	4 batteries 1.5V type LR6-AA-AM3-MN 1500
------------	------------------------------------------

ELECTRICAL FEATURES:

Conversion:	AC 16 Bit, TRMS
Sample frequency:	64 sample/period

MECHANICAL FEATURES:

Dimensions:	240(W) x 100(L) x 45(D) mm
Weight (included batteries):	about 450g

WORKING ENVIRONMENTAL CONDITIONS:

Reference temperature:	23°C ± 5°C
Working temperature:	0° ÷ 40°C
Allowed relative humidity:	< 70% HR
Storage temperature:	-10 ÷ 60°C
Storage humidity:	< 70% HR

TEST VERIFIES REFERENCE STANDARDS:

Continuity test with 200mA:	IEC 61557-4
Insulation resistance:	IEC 61557-2
Earth resistance:	IEC 61557-5
RCDs test:	IEC 61557-6

GENERAL REFERENCE STANDARDS:

Safety of measuring instruments:	EN61010-1 + A2(1997)
Product type standard:	IEC61557-2, 3, 4, 5, 6
Insulation:	class 2 (double insulation)
Pollution degree:	2
Overvoltage category:	CAT III 550V AC Phase - Ground CAT III 550V AC Phase - Phase
Use:	internal use; max altitude: 2000m
EMC:	EN61326-1 (1998) + A1 (1999)

This instrument complies with the requirements of the European Low Voltage Directives 2006/95/EEC (LVD) and EMC 2004/108/EEC



Zone Acticentre - CRT2 - CS 10210
156/220 Rue des Famards - 59273 FRETIN
Téléphone : 03.20.62.06.80
Télécopie : 03.20.96.95.62
<http://www.dimelco.com>