

## In-Transit Temperature Recorder

<b>Temperature Range</b>	Standard Model: -20°F to 100°F (-29°C to 38°C) High Range Model: 32°F to 150°F (0°C to 65°C) Low Range Model: -40°F to 80°F (-40°C to 27°C)
<b>Accuracy</b>	±2°F (±1°C) or better
<b>Sensor</b>	Bi-metal coil
<b>Chart</b>	Pressure sensitive, total length 36 inches (91.4cm), dual scale °F/°C
<b>Drive</b>	Solid state quartz motor
<b>Time Keeping Accuracy/Clock Motor</b>	Average ±20 seconds a month
<b>Battery</b>	AA Alkaline - high range models AA Carbon Zinc - standard models AA Lithium - low range model
<b>Shelf Life</b>	3 years
<b>Size</b>	5.5 in (L) x 4 in (W) x 2.5 in (H), 13.5 cm (L) x 10 cm (W) x 6.3 cm (H)
<b>Weight</b>	6.98oz. (198g)
<b>Case Lot Size/ Weight</b>	20 recorders per case/ 11lbs. (4.9kg)
<b>Certification/ calibration</b>	CE mark by T.U.V., traceable to N.I.S.T.
DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system	
PATENT NO. 4,990,940	



Models	5-Day	10-Day	20-Day	30-Day	40-Day	60-Day	90-Day
<b>Standard Range</b>	16000	16100	16200	16300	16350	16400	16500
<b>High Range</b>	16002	16102	16202	16302		16402	16502
<b>Low Range</b>	16004	16104	16203			16403	

- New 2 part document for ease of use
- New improved pull tab designed to make it easier to START
- Dual scale °F/°C chart
- Bilingual operation instructions
- Patented design guarantees recording trace stops at end of trip
- Lighter weight by 2 lbs per case
- Serial number on each unit for traceability



Zone Acticentre - CRT2 - CS 10210  
156/220 Rue des Famards - 59273 FRETIN  
Téléphone : 03.20.62.06.80  
Télécopie : 03.20.96.95.62  
<http://www.dimelco.com>