

Convir OS101 Series Low Cost Non-Contact Temperature Sensor

- ◆ -18 to 538°C Measurement Range
- ◆ Adjustable Emissivity From 0.10 to 1.0
- ◆ Fast, Accurate, Repeatable Readings
- ◆ Type K Thermocouple, 0 to 5 V DC, 4 to 20 mA or 1 mV/Deg. Analogue Output Models
- ◆ Rugged, Miniature Industrial Design with Remote Sensor Head
- ◆ User Adjustable High or Low Alarm Standard
- ◆ IP65 Metal Housing

The new Convir OS101 Series temperature measurement system features a remotely mounted infrared temperature sensor and high performance microprocessor based signal conditioner.

The OS101's miniature sensor head design is ideal for measuring temperature in confined, hard-to-reach places and harsh environments. The sensor head is connected to the main electronics housing via a 1.8 m shielded cable standard on all models.

The signal conditioners main electronics are mounted in a rugged IP65 rated diecast aluminium housing and feature adjustable emissivity, linear voltage, current or type K thermocouple output calibrated for the temperature range of -18 to 538°C. A user adjustable high/low alarm output is standard on all models.

Calex Electronics Limited

PO Box 2, Leighton Buzzard
Bedfordshire, England LU7 4AZ
Tel: +44 (0)1525 373178/853800
Fax: +44 (0)1525 851319
Lo-call Tel: 0845 3108053
E-mail: info@calex.co.uk
Online: <http://www.calex.co.uk>



Each OS101 comes complete with sensor head and 1.8 m (6') cable, sensor head mounting nut, main electronics housing and operator's manual.

GENERAL SPECIFICATIONS

Accuracy	±2% of reading or 2°C whichever is greater
Repeatability	±1% of reading
Spectral Range	8 to 14 µm
Response Time	150 ms (0 to 63% of final reading)
Emissivity Range	0.10 to 1.0
Field of View	6:1
Open Aperture	10 mm
Ambient Operating Range	
Main electronics	0 to 50°C
Sensor head	0 to 70°C
High temp sensor head (-HT)	0 to 85°C
Sensor Head with OS100-WC	0 to 200°C
Power	12 to 24 V DC
Temperature Range	-18 to 538°C
Alarm	Adjustable, open drain (100 mA)
Transmitter Output	Type K thermocouple, 1 mV/deg, 0 to 5 V DC or 4 to 20 mA
Electronics Housing	IP65, diecast aluminium
Sensor Head Cable Length	1.8 m standard
Dimensions	11.4 x 6.3 x 3 cm
Weight	272 g
Sensor Head	2.5 dia. x 6.3 cm long with 3/4 -16 UNF thread

ACCESSORIES

Model Number	Description
OS100-MB	Mounting Bracket
OS100-DR	DIN Rail Mounting Adaptor
OS100-AP	Air Purge Collar
OS100-WC	Water Cooling Jacket, up to 200°C
OS100-LS	Laser Sighting Accessory
OS100-CA15FT	Sensor Head Extension Cable 4.6 m
OS100-CA25FT	Sensor Head Extension Cable 7.6 m
TX8-100	Power / Output Cable 30 m
PSU-93-UK	DC Power Supply with UK Plug
PSU-93-EU	DC Power Supply with Euro Plug
CAL-80-IR	Traceable Calibration Certificate

TO ORDER (SPECIFY MODEL NO.)

Model Number	Description
OS101-MV-*	Transmitter with 1 mV/°C or °F output
OS101-K	Transmitter with type K thermocouple output
OS101-V1	Transmitter with 0 to 5 V DC output
OS101-MA	Transmitter with 4 to 20 mA output

(*) Insert F for mV/°F or C for mV/°C output

Insert -HT to model number for high temperature sensor head. Ordering Example: OS101-MA + OS100-LS + OS100-CA15FT, is a transmitter with 4 to 20 mA output, laser sighting accessory and 4.6 m sensor head extension cable.